



20' Offshore Container
20' x 8' x 8'6"
DNV/ISO Corner Castings
Corrugated Panel



DNV Certification Note 2.7-1: Offshore Containers
 BS EN 12079: Offshore Containers
 In support of IMO MSC/Circ. 860
 ISO/TC 104

The Customs Convention on Containers CCC/TIR
 The Convention for Safety Containers CSC
 Classification Society: Lloyd's Register
 Classification by Det Norske Veritas available by Special Order



Mobilization Packet :
Original Certificates and Full Data Book



DNV/ISO Corner Casting

Stackable Container

Allows for any intermodal means of transportation
 Handling Options: Forklift, Crane or Top Lift
 Truck, Rail, Commercial Ocean or barge



Includes

DNV Certified IWRC Wire Rope Lifting Sling

Equipped with Crosby Safety Pin Bow Shackles

And Flemish Splice, steel sleeves

DNV 2.7-1 / EN13414 / ASME B30.9

Uniquely numbered, tagged and certified



Dimensions

L x W x H

20' x 8' x 8'6"

External	Internal	Capacity
6058 mm (20')	5899 mm (19' 14")	30.8 Cu.m
2438 mm (8' 0")	2326 mm (7' 7")	(1087 Cu. ft)
2591 mm (8' 6")	2223 mm (7' 3")	

Door Opening: 2,218 mm W x 2,198 mm H

Ratings

As ISO	As Offshore
24,000 kg 52,910 lb	Max Gross 30,100 lb 13,650 kg
20,350 kg 44,860 lb	Payload 22,050 lb 10,000 kg
3,650 kg 8,050 lb	Tare (+/- 2%) 8,050 lb 3,650 kg