



# 20' Offshore Container 20' x 8' x 8'6"

DNV/ISO Corner Castings  
Double Door



DNV Certification Note 2.7-1: Offshore Containers

BS EN 12079: Offshore Containers

In support of IMO MSC/Circ. 860

ISO/TC 104

The Customs Convention on Containers CCC/TIR

The Convention for Safety Containers CSC

Classification Society: Lloyd's Register

Classification by Det Norske Veritas available by Special Order

**Mobilization Packet :**

**Original Certificates and Full Data Book**



## DNV/ISO Corner Casting

Stackable Container

Allows for any intermodal means of transportation

Handling Options: Forklift, Crane or Top Lift

Truck, Rail, Commercial Ocean or barge

**Includes**

**DNV Certified IWRC Wire Rope Lifting Sling**

Equipped with Crosby Safety Pin Bow Shackles

And Flemish Splice, steel sleeves

DNV 2.7-1 / EN13414 / ASME B30.9

Uniquely numbered, tagged and certified

### Dimensions

L x W x H

20' x 8' x 8'6"

#### External

6058 mm (20')

2438 mm (8' 0")

2591 mm (8' 6")

#### Internal

5848 mm (19' 2 15/64")

2218 mm (7' 3 5/16")

2218 mm (7' 3 5/16")

#### Capacity

28.8 Cu.m

(1017 Cu. ft)

**Door Opening: 2,218 mm W x 2,198 mm H**

### Ratings

As ISO

24,000 kg 52,910 lb

19,500 kg 42,990 lb

4,500 kg 9,920 lb

As Offshore

Max Gross 36,375 lb 16,500 kg

Payload 26,455 lb 12,000 kg

Tare (+/- 2%) 9,920 lb 4,500 kg

