



**20' Offshore Container**  
**20' x 8' x 8'6"**  
**Open Side**

*DNV/ISO Corner Castings*  
*Corrugated Panel*

DNV Certification Note 2.7-1: Offshore Containers

BS EN 12079: Offshore Containers

In support of IMO MSC/Circ. 860

ISO/TC 104

The Customs Convention on Containers CCC/TIR

The Convention for Safety Containers CSC

Classification Society: Lloyd's Register

Classification by Det Norske Veritas available by Special Order

**Mobilization Packet :**

**Original Certificates and Full Data Book**

**DNV/ISO Corner Casting**

Stackable Container

Allows for any intermodal means of transportation

Handling Options: Forklift, Crane or Top Lift



**Includes**

DNV Certified IWRC Wire Rope Lifting Sling

Equipped with Crosby Safety Pin Bow Shackles

And Flemish Splice, steel sleeves

DNV 2.7-1 / EN13414 / ASME B30.9

Uniquely numbered, tagged and certified



**Dimensions**

L x W x H

20' x 8' x 8'6"

External	Internal	Capacity
6058 mm (20')	5893 mm (19'4")	28.8 Cu.m
2438 mm (8' 0")	2270 mm (7' 5")	(1017 Cu. ft)
2591 mm (8' 6")	2153 mm (7' 3/4")	

End Door Opening: 2,114 mm W x 2,128 mm H

Side Door Opening: 5,702 mm W x 2,053 mm H

**Ratings**

As ISO		As Offshore	
24,000 kg	52,910 lb	Max Gross	35,270 lb 16,000 kg
19,300 kg	42,550 lb	Payload	24,910 lb 11,300 kg
4,700 kg	10,360 lb	Tare (+/- 2%)	10,360 lb 4,700 kg